
















COLORTONE FINE FISSURED

EDGE DETAIL	BOARD																																						
																																							
THICKNESS (mm)	15																																						
MODULES (mm)	600 x 600 9121MBK																																						
SUSPENSION SYSTEMS	Prelude 24 XL ² / TL ² Prelude 24 CR / TL ² Prelude 24 Sixty ² XL ² / TL ²																																						
COLOURS	 Black (BK)																																						
SUSTAINABILITY	 51				 A		 E1																																
ACOUSTICS	 EN ISO 10848-2 & EN ISO 717-1		 EN ISO 354 & EN ISO 11654		<table border="1"> <thead> <tr> <th rowspan="2"></th> <th rowspan="2">D_{nfw}</th> <th rowspan="2">α_w</th> <th rowspan="2">Class</th> <th rowspan="2">NRC</th> <th colspan="6">Hz α_p</th> </tr> <tr> <th>125</th> <th>250</th> <th>500</th> <th>1000</th> <th>2000</th> <th>4000</th> </tr> </thead> <tbody> <tr> <td>Board 15 mm</td> <td>36 dB</td> <td>0.60 (H)</td> <td>C</td> <td>0.60</td> <td>0.40</td> <td>0.40</td> <td>0.55</td> <td>0.75</td> <td>0.75</td> <td>0.75</td> </tr> </tbody> </table>								D_{nfw}	α_w	Class	NRC	Hz α_p						125	250	500	1000	2000	4000	Board 15 mm	36 dB	0.60 (H)	C	0.60	0.40	0.40	0.55	0.75	0.75	0.75
	D_{nfw}	α_w	Class	NRC	Hz α_p																																		
					125	250	500	1000	2000	4000																													
Board 15 mm	36 dB	0.60 (H)	C	0.60	0.40	0.40	0.55	0.75	0.75	0.75																													
FIRE REACTION		EEA Euroclass A2-s1, d0 <small>EN 13501-1</small>				RUS KM1 (G1, V1, D1, T1) <small>FZ 123</small>																																	
OTHER PERFORMANCES & FEATURES	 $\lambda = 0.060 \text{ W/m K}$ <small>EN 12667 & ISO 8301</small>	 95% RH	 3.4 kg/m ²		30YEAR system guarantee																																		
CUSTOM OPTIONS	 Colours ¹ ¹ Prelude suspension systems are available in following standard colours: Black (BK), Silver Grey RAL9006 (SG), Brass (BS), Chrome (CE), White RAL9010 (WR). A choice of over 180 RAL colours is available as a special order.																																						