



EDGE DETAIL BOARD



THICKNESS (mm) 15/18

MODULES (mm)	600 x 600 x 152695DBK2695DCG2695DNY2695DMT
	625 x 625 x 182404DBK2404DCG2404DNY2404DMT
	1200 x 600 x 152696MBK2696MCG2696MNY2696MMT
	1250 x 625 x 182405DBK2405DCG2405DNY2405DMT

SUSPENSION SYSTEMS
 Prelude 24 XL² / TL²
 Prelude 24 CR / TL²
 Prelude 24 Sixty² XL² / TL²

COLOURS

Black (BK)

Cement (CG)

Navy (NY)

Metal (MT)

SUSTAINABILITY

20

A

E1

ACOUSTICS

				Hz α_p							
	D_{ncw}	R_w	α_w	Class	NRC	125	250	500	1000	2000	4000
• Board 15 mm	-	7 dB	1.00	A	0.95	0.40	0.90	1.00	0.90	1.00	1.00
• Board 18 mm	24 dB	-	1.00	A	0.95	0.40	0.85	1.00	0.90	1.00	0.95

FIRE REACTION

EEA	Euroclass A1 (Black, Navy)	RUS	KM1 (G1, V1, D1, T1)
	Euroclass A2-s1,d0 (Cement)	FZ	FZ 123
	Euroclass A2-s2,d0 (Metal)		

EN 13501-1

OTHER PERFORMANCES & FEATURES

$\lambda = 0.033 \text{ W/m K}$
EN 12667 & ISO 8301

95% RH

1.2 kg/m² Board (15 mm)
 1.3 kg/m² Board (18 mm)

30YEAR system guarantee

BIM READY

CUSTOM OPTIONS

Colours¹

Dimensions

¹ Prelude suspension systems are available in following standard colours:
 Black (BK), Silver Grey RAL9006 (SG), Brass (BS), Chrome (CE), White RAL9010 (WR).
 A choice of over 180 RAL colours is available as a special order.